

# OSRAM KRBTQDLP61.3A

## Datasheet

Discontinued

Published by **ams-OSRAM AG**

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0


[ams-osram.com](http://ams-osram.com)

© All rights reserved



Micro SIDELED™ M4518

# KRBT QDLP61.3A - Reverse Mount



To fulfill the needs for pachinko- and gaming applications, this product is especially designed to achieve easy white binning and to reach high ESD level.



## Applications

- Access control & security
- Factory automation
- Home & building automation
- Material processing
- Projection & display
- Robotics

## Features

- Chip technology: Thinfilm / UX:3
- Typ. Radiation: 120° (Lambertian emitter)
- Color:  $\lambda_{\text{dom}} = 621 \text{ nm}$  (● red);  $\lambda_{\text{dom}} = 464 \text{ nm}$  (● blue);  $\lambda_{\text{dom}} = 530 \text{ nm}$  (● true green)
- Corrosion Robustness Class: 1B
- ESD: 8 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)
- Color:  $x = 0.245$ ,  $y = 0.23$  acc. to CIE 1931 (white)
- Typ. Luminous Intensity: 2.450 mcd (white), 700 mcd (red), 350 mcd (blue), 1.400 mcd (true green)

---

## Ordering Information

Type	Mounting Methode	Ordering Code
KRBTQDLP61.3A-5B5C-CH-F	Reverse	Q65112A7228

---

## Maximum Ratings

Parameter	Symbol		Values	Values	Values
			● red	● blue	● true green
Operating Temperature	$T_{op}$	min.	-40 °C	-40 °C	-40 °C
		max.	85 °C	85 °C	85 °C
Storage Temperature	$T_{stg}$	min.	-40 °C	-40 °C	-40 °C
		max.	85 °C	85 °C	85 °C
Junction Temperature	$T_j$	max.	115 °C	115 °C	115 °C
Forward Current $T_s = 25\text{ °C}$	$I_F$	max.	30 mA	30 mA	30 mA
Surge Current $t \leq 10\ \mu\text{s}; D = 0.005; T_s = 25\text{ °C}$	$I_{FS}$	max.	100 mA	100 mA	100 mA
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)	$V_{ESD}$		8 kV	8 kV	8 kV
Reverse voltage <sup>1)</sup>	$V_R$		Not designed for reverse operation	Not designed for reverse operation	Not designed for reverse operation

## Characteristics


$I_F$  (● red) = 20 mA;  $I_F$  (● blue) = ;  $I_F$  (● true green) = ;  $T_S = 25\text{ °C}$

Parameter	Symbol		Values	Values	Values
			● red	● blue	● true green
Dominant Wavelength <sup>2)</sup>	$\lambda_{\text{dom}}$	typ.	621 nm	464 nm	530 nm
Spectral bandwidth at 50% $I_{\text{rel,max}}$	$\Delta\lambda$	typ.	18 nm	25 nm	33 nm
Viewing angle at 50% $I_V$	$2\phi$	typ.	120 °	120 °	120 °
Forward Voltage <sup>3)</sup> $I_F = 20\text{ mA}$	$V_F$	typ.	2.1 V	2.9 V	3.2 V
Reverse current <sup>1)</sup>	$I_R$		Not designed for reverse operation	Not designed for reverse operation	Not designed for reverse operation
Real thermal resistance junction/solderpoint <sup>4)</sup>	$R_{\text{thJS real}}$	typ. max.	490 K / W 590 K / W	200 K / W 240 K / W	290 K / W 350 K / W

## Brightness Groups

Group	Luminous Intensity <sup>5)</sup> $I_F = 20 \text{ mA}$ min. $I_v$	Luminous Intensity <sup>5)</sup> $I_F = 20 \text{ mA}$ max. $I_v$
5B	1800 mcd	2010 mcd
6B	2010 mcd	2240 mcd
7B	2240 mcd	2500 mcd
8B	2500 mcd	2800 mcd
5C	2800 mcd	3150 mcd

## Chromaticity Coordinate Groups




## Chromaticity Coordinate Groups

Group	Cx	Cy	Group	Cx	Cy	Group	Cx	Cy
C	0.2250	0.2232	E	0.2325	0.2532	G	0.2400	0.2832
	0.2175	0.1932		0.2250	0.2232		0.2325	0.2532
	0.2475	0.1932		0.2550	0.2232		0.2625	0.2532
	0.2550	0.2232		0.2625	0.2532		0.2700	0.2832
D	0.2550	0.2232	F	0.2625	0.2532	H	0.2700	0.2832
	0.2850	0.2232		0.2550	0.2232		0.2625	0.2532
	0.2775	0.1932		0.2850	0.2232		0.2925	0.2532
	0.2475	0.1932		0.2925	0.2532		0.3000	0.2832


### Relative Spectral Emission <sup>6)</sup>

$I_{rel} = f(\lambda); I_F = 20 \text{ mA}; T_S = 25 \text{ }^\circ\text{C}$




### Radiation Characteristic (horizontal) <sup>6)</sup>

$$I_{rel} = f(\varphi); T_S = 25\text{ }^\circ\text{C}$$



### Radiation Characteristic (vertical) <sup>6)</sup>


$$I_{rel} = f(\varphi); T_S = 25\text{ }^\circ\text{C}$$



Discontinued


**Forward current** <sup>6)</sup>

$I_F = f(V_F); T_S = 25\text{ °C}$




**Forward current** <sup>6)</sup>

$I_F = f(V_F); T_S = 25\text{ °C}$



**Forward current** <sup>6)</sup>


$I_F = f(V_F); T_S = 25\text{ °C}$



Discontinued


**Relative Luminous Intensity** <sup>6), 7)</sup>

$I_V/I_V(20\text{ mA}) = f(I_F); T_S = 25\text{ °C}$




**Relative Luminous Intensity** <sup>6), 7)</sup>

$I_V/I_V() = f(I_F); T_S = 25\text{ °C}$




**Relative Luminous Intensity** <sup>6), 7)</sup>

$I_V/I_V() = f(I_F); T_S = 25\text{ °C}$



**Relative Luminous Intensity** <sup>6), 7)</sup>


$I_V/I_V() = f(I_F); T_S = 25\text{ °C}$



Discontinued


### Dominant Wavelength <sup>6)</sup>

$$\Delta\lambda_{\text{dom}} = f(I_F); T_S = 25\text{ }^\circ\text{C}$$




### Dominant Wavelength <sup>6)</sup>

$$\Delta\lambda_{\text{dom}} = f(I_F); T_S = 25\text{ }^\circ\text{C}$$




### Chromaticity Coordinate Shift <sup>6)</sup>

$$\Delta Cx, \Delta Cy = f(I_F); T_S = 25\text{ }^\circ\text{C}$$




**Forward Voltage** <sup>6)</sup>

$$\Delta V_F = V_F - V_F(25\text{ }^\circ\text{C}) = f(T_j); I_F = 20\text{ mA}$$




**Forward Voltage** <sup>6)</sup>

$$\Delta V_F = V_F - V_F(25\text{ }^\circ\text{C}) = f(T_j);$$



**Forward Voltage** <sup>6)</sup>


$$\Delta V_F = V_F - V_F(25\text{ }^\circ\text{C}) = f(T_j);$$



Discontinued


Relative Luminous Intensity <sup>6)</sup>

$I_V/I_V(25\text{ °C}) = f(T_j); I_F = 20\text{ mA}$




Relative Luminous Intensity <sup>6)</sup>

$I_V/I_V(25\text{ °C}) = f(T_j);$




Relative Luminous Intensity <sup>6)</sup>

$I_V/I_V(25\text{ °C}) = f(T_j);$



Relative Luminous Intensity <sup>6)</sup>


$I_V/I_V(25\text{ °C}) = f(T_j);$



Discontinued


### Dominant Wavelength <sup>6)</sup>

$$\Delta\lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25\text{ }^\circ\text{C}) = f(T_j); I_F = 20\text{ mA}$$




### Dominant Wavelength <sup>6)</sup>

$$\Delta\lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25\text{ }^\circ\text{C}) = f(T_j);$$




### Dominant Wavelength <sup>6)</sup>

$$\Delta\lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25\text{ }^\circ\text{C}) = f(T_j);$$




### Chromaticity Coordinate Shift <sup>6)</sup>

$$\Delta C_x, \Delta C_y = f(T_j);$$




**Max. Permissible Forward Current** <sup>4)</sup>

$I_F = f(T)$ ; ● red




**Max. Permissible Forward Current** <sup>4)</sup>

$I_F = f(T)$ ; ● blue



**Max. Permissible Forward Current** <sup>4)</sup>


$I_F = f(T)$ ; ● true green



Discontinued


### Permissible Pulse Handling Capability

$I_F = f(t_p)$ ; D: Duty cycle; ● red




### Permissible Pulse Handling Capability

$I_F = f(t_p)$ ; D: Duty cycle; ● red



### Permissible Pulse Handling Capability


$I_F = f(t_p)$ ; D: Duty cycle; ● blue



Permissible Pulse Handling Capability

$I_F = f(t_p)$ ; D: Duty cycle; ● true green


KRBT QDLP61.3A - Reverse Mount




Permissible Pulse Handling Capability

$I_F = f(t_p)$ ; D: Duty cycle; ● true green

KRBT QDLP61.3A - Reverse Mount



Dimensional Drawing <sup>8)</sup>



C63062-A4294-A1-08


Further Information:

Approximate Weight: 8.9 mg


Corrosion test: Class: 1B  
Test condition: 25°C / 75 % RH / 200ppb SO<sub>2</sub>, 200ppb NO<sub>2</sub>, 10ppb H<sub>2</sub>S,  
10ppb Cl<sub>2</sub> / 21 days (EN 60068-2-60 (Method 4))

Electrical Internal Circuit

Polarity



Recommended Solder Pad <sup>8)</sup>



Component Location on Pad




E062.3010.213 -02

For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for ultra sonic cleaning. Handling Indication: The package is casted with silicone. Mechanical stress at the silicone surface of the unit should be avoided. Pickup the device at the plastic frame.

## Reflow Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E




Profile Feature	Symbol	Pb-Free (SnAgCu) Assembly			Unit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat <sup>*)</sup> 25 °C to 150 °C			2	3	K/s
Time $t_s$ $T_{Smin}$ to $T_{Smax}$	$t_s$	60	100	120	s
Ramp-up rate to peak <sup>*)</sup> $T_{Smax}$ to $T_p$			2	3	K/s
Liquidus temperature	$T_L$		217		°C
Time above liquidus temperature	$t_L$		80	100	s
Peak temperature	$T_p$		245	260	°C
Time within 5 °C of the specified peak temperature $T_p - 5$ K	$t_p$	10	20	30	s
Ramp-down rate* $T_p$ to 100 °C			3	6	K/s
Time 25 °C to $T_p$				480	s

Discontinued


All temperatures refer to the center of the package, measured on the top of the component  
 \*) slope calculation  $DT/Dt$ :  $Dt$  max. 5 s; fulfillment for the whole T-range

Taping <sup>8)</sup>



C63062-A4294-B1-05

**Tape and Reel** <sup>9)</sup>



**Reel Dimensions**

A	W	N <sub>min</sub>	W <sub>1</sub>	W <sub>2max</sub>	Pieces per PU
180 mm	12 + 0.3 / - 0.1 mm	60 mm	12.4 + 2 mm	18.4 mm	2000

Barcode-Product-Label (BPL)

**OSRAM** LX XXXX    BIN1: XX-XX-X-XXX-X

RoHS Compliant

(6P) BATCH NO: 1234567890 ML Temp    ST  
X    XXX °C X


(1T) LOT NO: 1234567890 (9D) D/C: 1234

(X) PROD NO: 123456789 (Q) QTY: 9999 (G) GROUP: XX-XX-X-X

Pack: RXX  
DEMY    XXX  
X\_X123\_1234.1234 X

OHA04563

Dry Packing Process and Materials <sup>8)</sup>




OHA00539

Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according JEDEC-STD-033.

Discontinued

Type Designation System



Discontinued

## Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **exempt group (exposure time 10000 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

For further application related information please visit <https://ams-osram.com/support/application-notes>

---

## Disclaimer

### Attention please!

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.

If printed or downloaded, please find the latest version on our website.

### Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

### Product and functional safety devices/applications or medical devices/applications

Our components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

Our products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using our components in product safety devices/ applications or medical devices/applications, buyer and/or customer has to inform our local sales partner immediately and we and buyer and /or customer will analyze and coordinate the customer-specific request between us and buyer and/or customer.

## Glossary

- 1) **Reverse Operation:** Not designed for reverse operation. Continuous reverse operation can cause migration and damage of the device.
- 2) **Wavelength:** Wavelengths are tested at a current pulse duration of 25 ms and a tolerance of  $\pm 1$  nm.
- 3) **Forward Voltage:** Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of  $\pm 0.1$  V.
- 4) **Thermal Resistance:**  $R_{th\ max}$  is based on statistic values ( $6\sigma$ ) used for Derating.
- 5) **Brightness:** Brightness values are measured during a current pulse of typically 25 ms, with an internal reproducibility of  $\pm 8$  % and an expanded uncertainty of  $\pm 11$  % (acc. to GUM with a coverage factor of  $k = 3$ ).
- 6) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 7) **Characteristic curve:** In the range where the line of the graph is broken, you must expect higher differences between single devices within one packing unit.
- 8) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with  $\pm 0.1$  and dimensions are specified in mm.
- 9) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

---

## Revision History

Version	Date	Change
1.4	2018-11-28	Chromaticity Coordinate Groups
1.5	2024-11-20	New Layout Applications
1.6	2026-06-03	Discontinued

Discontinued

---



EU RoHS and China RoHS compliant product

此产品符合欧盟 RoHS 指令的要求；  
按照中国的相关法规和标准，  
不含有毒有害物质或元素。

**Published by ams-OSRAM AG**

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0

[ams-osram.com](http://ams-osram.com)

© All rights reserved

**am** 

**OSRAM**