

OSRAM GW JTU9S2.KM

Datasheet

Published by **ams-OSRAM AG**

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0

ams-osram.com

© All rights reserved



DURIS™ E 2835

GW J TU9S2.KM

Experience next-level lighting performance with the DURIS™ E 2835 U9 Series. Engineered with a standard 2835 footprint, this pre-molded LED delivers outstanding values— combining advanced phosphor technology for superior efficiency, consistent and homogeneous illumination. Its capability of low current dimming and precise 3-step color control ensure uniformity – an important premium feature for professional indoor applications. DURIS™ E 2835 U9 series is a lighting solution that brings performance, reliability, and affordability for a superior system-level results.



Applications

- Indoor lighting

Features

- Package: white SMT package, colored diffused resin
- Color temperature: 1800K - 6500K
- CRI: 90 (min.), R9: 50 (min.)
- ESD: 2 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)
- Luminous Flux (@ 4000 K): typ. 78 lm @ 50mA; typ. 145 lm @ 100mA
- Luminous efficacy: typ. 182.5 lm/W @ 4000 K
- Stable Vf deep dimming at low driving current from 1mA

Ordering Information

Type	Color temperature	McAdams steps	Luminous Flux ¹⁾ $I_F = 50 \text{ mA}$ Φ_V	Ordering Code
GW J TU9S2.KM-JAJC-18S3-9C9D	1800 K	SDCM 3	40.0 ... 55.0 lm	Q65115A3077
GW J TU9S2.KM-JCJE-22S3-9C9D	2200 K	SDCM 3	50.0 ... 65.0 lm	Q65115A3075
GW J TU9S2.KM-JFKY-27S3-9C9D	2700 K	SDCM 3	65.0 ... 80.0 lm	Q65115A3078
GW J TU9S2.KM-JGKZ-30S3-9C9D	3000 K	SDCM 3	70.0 ... 85.0 lm	Q65115A3121
GW J TU9S2.KM-JGKZ-35S3-9C9D	3500 K	SDCM 3	70.0 ... 85.0 lm	Q65115A3096
GW J TU9S2.KM-KYKS-40S3-9C9D	4000 K	SDCM 3	75.0 ... 90.0 lm	Q65115A3081
GW J TU9S2.KM-KYKS-50S3-9C9D	5000 K	SDCM 3	75.0 ... 90.0 lm	Q65115A3082
GW J TU9S2.KM-JGKZ-57S3-9C9D	5700 K	SDCM 3	70.0 ... 85.0 lm	Q65115A3095
GW J TU9S2.KM-JGKZ-65S3-9C9D	6500 K	SDCM 3	70.0 ... 85.0 lm	Q65115A3083

Maximum Ratings

Parameter	Symbol		Values
Operating Temperature	T_{op}	min.	-40 °C
		max.	100 °C
Storage Temperature	T_{stg}	min.	-40 °C
		max.	100 °C
Junction Temperature	T_j	max.	125 °C
Forward Current $T_j = 25\text{ °C}$	I_F	min.	1 mA
		max.	125 mA
Reverse voltage ²⁾	V_R		Not designed for reverse operation
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)	V_{ESD}		2 kV

Note: Ensure the appropriate derating current is being used in order to maintain a junction temperature which is lower than the maximum allowable limit.

Characteristics

 $I_F = 50 \text{ mA}; T_J = 25 \text{ }^{\circ}\text{C}$


Parameter	Symbol		Values
Viewing angle at 50% I_v values for 0° , 90°	2ϕ	typ.	120°
Forward Voltage ³⁾	V_F	min.	8.40 V
		typ.	8.55 V
		max.	8.80 V
Reverse current ²⁾	I_R		Not designed for reverse operation
Color Rendering Index ⁴⁾	CRI	min.	90
Color Rendering Index (R9) ⁴⁾	CRI (R9)	min.	50
Electrical thermal resistance junction/solderpoint with efficiency $\eta_e = 51.1 \%$	$R_{thJS \text{ elec.}}$	typ.	15 K / W

Brightness Groups

Group	Luminous Flux ¹⁾ $I_F = 50 \text{ mA}$ min. Φ_V	Luminous Flux ¹⁾ $I_F = 50 \text{ mA}$ max. Φ_V
JA	40.0 lm	45.0 lm
JB	45.0 lm	50.0 lm
JC	50.0 lm	55.0 lm
JD	55.0 lm	60.0 lm
JE	60.0 lm	65.0 lm
JF	65.0 lm	70.0 lm
JG	70.0 lm	75.0 lm
KY	75.0 lm	80.0 lm
KZ	80.0 lm	85.0 lm
KS	85.0 lm	90.0 lm

Forward Voltage Groups

Group	Forward Voltage ³⁾ min. V_F	Forward Voltage ³⁾ max. V_F
9C	8.40 V	8.60 V
9D	8.60 V	8.80 V

Chromaticity Coordinate Groups ⁵⁾

Chromaticity Coordinate Groups

CCT	Center Cx	Center Cy	3step a	3step b	Ø
1800 K	0.5492	0.4082	0.0096	0.0046	47.3
2200 K	0.5020	0.4156	0.0072	0.004	39.9
2700 K	0.4577	0.4098	0.008	0.0041	54.1
3000 K	0.4339	0.4032	0.0086	0.0042	53.7
3500 K	0.4077	0.3929	0.0093	0.0042	53.9
4000 K	0.3818	0.3796	0.0094	0.0041	53.4
5000 K	0.3446	0.3551	0.0081	0.0035	59.8
5700 K	0.3287	0.3425	0.0072	0.0032	58.8
6500 K	0.3123	0.3282	0.0066	0.0027	58.1


Group Name on Label

Example: JA-40S3-9C

Brightness	Color Chromaticity	Forward Voltage
JA	40S3	9C


Relative Spectral Emission ⁶⁾

$\Phi_{\text{rel}} = f(\lambda)$; $I_F = 50 \text{ mA}$; $T_J = 25 \text{ }^\circ\text{C}$




Radiation Characteristics ⁶⁾

$I_{\text{rel}} = f(\varphi)$; $T_J = 25 \text{ }^\circ\text{C}$




Forward current ⁶⁾

$$I_F = f(V_F); T_J = 25\text{ °C}$$




Relative Luminous Flux ^{6), 7)}

$$\Phi_V / \Phi_V(50\text{ mA}) = f(I_F); T_J = 25\text{ °C}$$



Chromaticity Coordinate Shift ⁶⁾

$$\Delta Cx, \Delta Cy = f(I_F); T_J = 25\text{ °C}$$




Note:

Luminous flux and color point for $<10\text{ mA}$ are for reference purpose and subject to measurement tolerance. They are excluded from standard tolerance window


Forward Voltage ⁶⁾

$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 50\text{ mA}$$




Relative Luminous Flux ⁶⁾

$$\Phi_V / \Phi_V(25^\circ\text{C}) = f(T_j); I_F = 50\text{ mA}$$




Chromaticity Coordinate Shift ⁶⁾

$$\Delta C_x, \Delta C_y = f(T_j); I_F = 50\text{ mA}$$




Max. Permissible Forward Current ⁸⁾

$$I_F = f(T)$$



Dimensional Drawing ⁹⁾



general tolerance ± 0.1

lead finish Ag 


C67062-A0204-A9-01

Further Information:

Approximate Weight: 20.0 mg

Package marking: Cathode

Recommended Solder Pad ⁹⁾



E067.0346.04-01

For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for ultra sonic cleaning.

Reflow Soldering Profile

Product complies to MSL Level 3 acc. to JEDEC J-STD-020E



Profile Feature	Symbol	Pb-Free (SnAgCu) Assembly			Unit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat ^{*)} 25°C to 150°C			2	3	K/s
Time t_s T_{Smin} to T_{Smax}	t_s	60	100	120	s
Ramp-up rate to peak ^{*)} T_{Smax} to T_p			2	3	K/s
Liquidus temperature	T_L		217		$^{\circ}\text{C}$
Time above liquidus temperature	t_L		80	100	s
Peak temperature	T_p		245	260	$^{\circ}\text{C}$
Time within 5°C of the specified peak temperature $T_p - 5\text{ K}$	t_p	10	20	30	s
Ramp-down rate [*] T_p to 100°C			3	6	K/s
Time 25°C to T_p				480	s

All temperatures refer to the center of the package, measured on the top of the component

^{*} slope calculation DT/Dt : Dt max. 5 s; fulfillment for the whole T-range

Technical drawing of a cathode grid assembly. The top view shows a rectangular plate with a total width of 8 and a total length of 17.75. The plate is divided into seven sections by vertical lines, with a central section of width 3.16 and side sections of width 4. The top view also shows a central circular feature with a diameter of $\phi 1.50$ and a central rectangular feature with a width of 3.77 and a height of 1.75. The side view shows a cross-section of the plate with a total thickness of 1 and a central rectangular feature with a width of 3.77 and a height of 1.75. The side view also shows a central circular feature with a diameter of $\phi 1.1$ and a central rectangular feature with a width of 3.77 and a height of 1.75. The side view is labeled 'cathode side'.

C67062-A0204-B12-01

Tape and Reel ¹⁰⁾



Reel Dimensions

A	W	N _{min}	W ₁	W _{2 max}	Pieces per PU
330 mm	8 + 0.3 / - 0.1 mm	60 mm	8.4 + 2 mm	14.4 mm	10000

Barcode-Product-Label (BPL)

OSRAM

LX XXXX BIN1: XX-XX-X-XXX-X

RoHS Compliant

(6P) BATCH NO: 1234567890

(1T) LOT NO: 1234567890 (9D) D/C: 1234

(X) PROD NO: 123456789 (Q) QTY: 9999 (G) GROUP: XX-XX-X-X


ML Temp ST
X XXX °C X

Pack: RXX
DEMY XXX
X_X123_1234.1234 X

EXAMPLE

OHA04563

Dry Packing Process and Materials



Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according JEDEC-STD-033.

Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **moderate risk (exposure time 0.25 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

This device is designed for specific/recommended applications only. Please consult OSRAM Opto Semiconductors Sales Staff in advance for detailed information on other non-recommended applications (e.g. automotive).

Change management for this component is aligned with the requirements of the lighting market.

For further application related information please visit <https://ams-osram.com/support/application-notes>

Eye safety classification at moderate risk is at maximum driving current.

Disclaimer

Attention please!

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.

If printed or downloaded, please find the latest version on our website.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product and functional safety devices/applications or medical devices/applications

Our components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

Our products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using our components in product safety devices/ applications or medical devices/applications, buyer and/or customer has to inform our local sales partner immediately and we and buyer and /or customer will analyze and coordinate the customer-specific request between us and buyer and/or customer.

Glossary

- 1) **Brightness:** Brightness values are measured during a current pulse of typically 45 ms (measurement starts with a delay of 25 ms), with a tolerance of +/- 5%.
- 2) **Reverse Operation:** Not designed for reverse operation. Continuous reverse operation can cause migration and damage of the device.
- 3) **Forward Voltage:** The Forward voltage is measured during a current pulse duration of typically 45 ms (measurement starts with a delay of 25 ms) with a tolerance of $\pm 0.05V$.
- 4) **Color reproduction index:** Color reproduction index values (CRI-RA) are measured during a current pulse of typically 45 ms (measurement starts with a delay of 25 ms) and with a tolerance of ± 2 . CRI-R9 are measured during a current pulse of typically 45 ms (measurement starts with a delay of 25 ms) and the 4000K with a tolerance of ± 6 .
- 5) **Chromaticity coordinate groups:** Chromaticity coordinate groups are measured during a current pulse duration of typically 10ms with a tolerance of ± 0.005 .
- 6) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 7) **Characteristic curve:** In the range where the line of the graph is broken, you must expect higher differences between single devices within one packing unit.
- 8) **Thermal Resistance:** $R_{th\ max}$ is based on statistic values (6σ) used for Derating.
- 9) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ± 0.1 and dimensions are specified in mm.
- 10) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

Revision History

Version	Date	Change
1.0	2026-02-10	Initial Version
1.0	2026-06-24	Initial Version
1.1	2026-07-07	Electro - Optical Characteristics (Diagrams)



EU RoHS and China RoHS compliant product

此产品符合欧盟 RoHS 指令的要求；
按照中国的相关法规和标准，
不含有毒有害物质或元素。

Published by ams-OSRAM AG

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0

ams-osram.com

© All rights reserved

am

OSRAM