

OSRAM GD PUBRA1.15

Datasheet

Published by ams-OSRAM AG
Tobelbader Strasse 30, 8141 Premstaetten, Austria
Phone +43 3136 500-0
ams-osram.com
© All rights reserved

am  **OSRAM**

OSCONIQ™ P 3737 (2W)

GD PUBRA1.15 (G3)

OSCONIQ™ P 3737 Batwing delivers exceptional light uniformity, enhanced brightness and long lifetime. Featuring a unique batwing radiation profile, it ensures wide-angle coverage with reduced hotspots, making it ideal for large-area horticultural lighting. Available in a range of targeted wavelengths, the P 3737 Batwing offers design flexibility and spectral precision to meet the dynamic needs of modern growers.



Applications

- Agriculture & horticulture
- Entertainment
- Indoor lighting
- Outdoor & industrial lighting

Features

- Package: SMD epoxy package with silicone lens
- ESD: 8 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)
- Typ. Radiation: 140°
- Radiant Flux (@ 700mA): typ. 1448 mW @ 85°C
- Radiant Efficiency (@ 700mA): typ. 73.1% @ 85°C
- Photon Flux (@ 700mA): typ. 5.41 µmol/s @ 85°C
- Photon Flux Efficacy (@ 700mA): typ. 2.73 µmol/J @ 85°C

Ordering Information

Type	Photon Flux ¹⁾ $I_F = 700 \text{ mA}$ Φ_P	Ordering Code
GD PUBRA1.15-T1T4-24-1-D	5.10 ... 5.90 $\mu\text{mol/s}$	Q65115A3136

Maximum Ratings

Parameter	Symbol	Values	
Operating Temperature	T_{op}	min.	-40 °C
		max.	125 °C
Storage Temperature	T_{stg}	min.	-40 °C
		max.	125 °C
Junction Temperature	T_j	max.	135 °C
Forward current	I_F	min.	100 mA
		max.	2000 mA
Surge Current $t \leq 10 \mu\text{s}$; $D = 0.005$; $T_j = 85 \text{ }^\circ\text{C}$	I_{FS}	max.	2500 mA
Reverse voltage ²⁾	V_R	Not designed for reverse operation	
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)	V_{ESD}	8 kV	

Characteristics

$I_F = 700 \text{ mA}$; $T_J = 85 \text{ }^\circ\text{C}$

Parameter	Symbol	Values
Peak Wavelength	λ_{peak}	typ. 446 nm
Dominant Wavelength ³⁾ $I_F = 700 \text{ mA}$	λ_{dom}	min. 444 nm typ. 450 nm max. 457 nm
Spectral Bandwidth at 50% $I_{\text{rel,max}}$	$\Delta\lambda$	typ. 18 nm
Viewing angle at 50% I_V	2ϕ	typ. 140 °
Forward Voltage ⁴⁾ $I_F = 700 \text{ mA}$	V_F	min. 2.75 V typ. 2.83 V max. 2.95 V
Reverse current ²⁾	I_R	Not designed for reverse operation
Electrical thermal resistance junction/solderpoint with efficiency $\eta_e = 73.1 \text{ \%}$	$R_{\text{thJS elec.}}$	typ. 1.1 K / W

Brightness Groups

Group	Photon Flux ¹⁾ PF/W			Total Radiant Flux min. Φ_E	Total Radiant Flux max. Φ_E
	$I_F = 700$ mA min. Φ_P	$I_F = 700$ mA max. Φ_P	typ.		
T1	5.10 $\mu\text{mol/s}$	5.30 $\mu\text{mol/s}$	2.62 $\mu\text{mol/J}$	1,368 mW	1,422 mW
T2	5.30 $\mu\text{mol/s}$	5.50 $\mu\text{mol/s}$	2.73 $\mu\text{mol/J}$	1,422 mW	1,475 mW
T3	5.50 $\mu\text{mol/s}$	5.70 $\mu\text{mol/s}$	2.83 $\mu\text{mol/J}$	1,475 mW	1,529 mW
T4	5.70 $\mu\text{mol/s}$	5.90 $\mu\text{mol/s}$	2.93 $\mu\text{mol/J}$	1,529 mW	1,583 mW

Note: [*] Photon Flux includes wavelengths between 280 and 800 nm.

Note: [**] Radiant Flux values are for reference only.

Forward Voltage Groups

Group	Forward Voltage ⁴⁾		Forward Voltage ⁴⁾ $I_F = 700$ mA max. V_F
	$I_F = 700$ mA min.	V_F	
1W		2.75 V	2.80 V
1Y		2.80 V	2.85 V
1Z		2.85 V	2.90 V
2A		2.90 V	2.95 V

Wavelength Groups

Group	Dominant Wavelength ³⁾		Dominant Wavelength ³⁾ $I_F = 700$ mA max. λ_{dom}
	$I_F = 700$ mA min.	λ_{dom}	
2	444 nm		449 nm
3	449 nm		453 nm
4	453 nm		457 nm

Group Name on Label


Example: T1-2-1W

Brightness	Wavelength	Forward Voltage
------------	------------	-----------------

T1	2	1W
----	---	----


Relative Spectral Emission ⁵⁾

$I_{\text{rel}} = f(\lambda)$; $I_F = 700 \text{ mA}$; $T_J = 85^\circ \text{C}$




Radiation Characteristics ⁵⁾

$I_{\text{rel}} = f(\varphi)$; $T_J = 85^\circ \text{C}$




Forward current ⁵⁾

$I_F = f(V_F)$; $T_J = 85^\circ\text{C}$




Relative Photon Flux ^{5), 6)}

$\Phi_P / \Phi_{P(700 \text{ mA})} = f(I_F)$; $T_J = 85^\circ\text{C}$




Dominant Wavelength ⁵⁾

$\Delta\lambda_{\text{dom}} = f(I_F)$; $T_J = 85^\circ\text{C}$




Forward Voltage ⁵⁾

$$\Delta V_F = V_F - V_F(85^\circ\text{C}) = f(T_j); I_F = 700 \text{ mA}$$




Relative Photon Flux ⁵⁾

$$\Phi_p/\Phi_p(85^\circ\text{C}) = f(T_j); I_F = 700 \text{ mA}$$




Dominant Wavelength ⁵⁾

$$\Delta \lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(85^\circ\text{C}) = f(T_j); I_F = 700 \text{ mA}$$






Max. Permissible Forward Current ⁷⁾

$$I_F = f(T)$$



Dimensional Drawing ⁸⁾



General tolerance ± 0.1

Lead finish Au 


C69062-A0052-A4..-01

Further Information:

Approximate Weight: 44.0 mg

ESD advice: The device is protected by ESD device which is connected in parallel to the Chip.


Recommended Solder Pad ⁸⁾



For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for ultra sonic cleaning.

Reflow Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E




Profile Feature	Symbol	Pb-Free (SnAgCu) Assembly			Unit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat*) 25 °C to 150 °C			2	3	K/s
Time t_s T_{Smin} to T_{Smax}	t_s	60	100	120	s
Ramp-up rate to peak*) T_{Smax} to T_p			2	3	K/s
Liquidus temperature	T_L	217			°C
Time above liquidus temperature	t_L	80	100	100	s
Peak temperature	T_p	245	260	260	°C
Time within 5 °C of the specified peak temperature T_p - 5 K	t_p	10	20	30	s
Ramp-down rate* T_p to 100 °C			3	6	K/s
Time 25 °C to T_p			480	480	s

All temperatures refer to the center of the package, measured on the top of the component


* slope calculation DT/Dt : Dt max. 5 s; fulfillment for the whole T-range

Taping ⁸⁾



C69062-A0052-B8-02


Tape and Reel ⁹⁾



Reel Dimensions


A	W	N_{\min}	W_1	$W_{2\max}$	Pieces per PU
330 mm	12 + 0.3 / - 0.1 mm	60 mm	12.4 + 2 mm	18.4 mm	3000

Barcode-Product-Label (BPL)



OHA04563

Dry Packing Process and Materials



OHA00539

Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according to JEDEC-STD-033.

Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **moderate risk (exposure time 0.25 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

This device is designed for specific/recommended applications only. Please consult OSRAM Opto Semiconductors Sales Staff in advance for detailed information on other non-recommended applications (e.g. automotive).

Change management for this component is aligned with the requirements of the lighting market.

For further application related information please visit <https://ams-osram.com/support/application-notes>

Disclaimer

Attention please!

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.
If printed or downloaded, please find the latest version on our website.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product and functional safety devices/applications or medical devices/applications

Our components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

Our products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using our components in product safety devices/applications or medical devices/applications, buyer and/or customer has to inform our local sales partner immediately and we and buyer and /or customer will analyze and coordinate the customer-specific request between us and buyer and/or customer.

Glossary

- 1) **Brightness:** Brightness values are measured during a current pulse of typically 10 ms, with a tolerance of \pm 7%.
- 2) **Reverse Operation:** Not designed for reverse operation. Continuous reverse operation can cause migration and damage of the device.
- 3) **Wavelength:** The wavelength is measured at a current pulse of typically 10 ms, with a tolerance of \pm 0.5 nm.
- 4) **Forward Voltage:** The Forward voltage is measured during a current pulse duration of typically 1 ms with a tolerance of \pm 0.05V .
- 5) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 6) **Characteristic curve:** In the range where the line of the graph is broken, you must expect higher differences between single devices within one packing unit.
- 7) **Thermal Resistance:** $R_{th\ max}$ is based on statistic values (6σ) used for Derating.
- 8) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ± 0.1 and dimensions are specified in mm.
- 9) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

Revision History

Version	Date	Change
1.0	2026-02-12	Initial Version



EU RoHS and China RoHS compliant product

此产品符合欧盟 RoHS 指令的要求；

按照中国的相关法规和标准，

不含有毒有害物质或元素。

Published by ams-OSRAM AG

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0

ams-osram.com

© All rights reserved

am  **OSRAM**