

# OSRAM GW PUBRA1.HW

## Datasheet


Published by ams-OSRAM AG  
Tobelbader Strasse 30, 8141 Premstaetten, Austria  
Phone +43 3136 500-0  
[ams-osram.com](http://ams-osram.com)  
© All rights reserved

**am**  **OSRAM**

OSCONIQ™ P 3737 (2W)

# GW PUBRA1.HW (G3)

OSCONIQ™ P 3737 Batwing delivers exceptional light uniformity, enhanced brightness and long lifetime. Featuring a unique batwing radiation profile, it ensures wide-angle coverage with reduced hotspots, making it ideal for large-area horticultural lighting. Available in a range of targeted wavelengths, the P 3737 Batwing offers design flexibility and spectral precision to meet the dynamic needs of modern growers.



## Applications

- Agriculture & horticulture
- Entertainment
- Indoor lighting
- Outdoor & industrial lighting

## Features

- Package: SMD epoxy package with silicone lens
- ESD: 8 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)
- Typ. Radiation: 140°
- Radiant Flux (@ 700mA): typ. 1140 mW @ 85°C (M3 Bin)
- Radiant Efficiency (@ 700mA): typ. 57.5% @ 85°C (M3 Bin)
- Photon Flux (@ 700mA): typ. 5.01 µmol/s @ 85°C (M3 Bin)
- Photon Flux Efficacy (@ 700mA): typ. 2.53 µmol/J @ 85°C (M3 Bin)

## Ordering Information

Type	Photon Flux <sup>1)</sup> $I_F = 700 \text{ mA}$ $\Phi_P$	Ordering Code
GW PUBRA1.HW-S5T2-M1-1-D	4.65 ... 5.50 $\mu\text{mol/s}$	Q65115A3133
GW PUBRA1.HW-S5T2-M2-1-D	4.65 ... 5.50 $\mu\text{mol/s}$	Q65115A3132
GW PUBRA1.HW-S5T2-M3-1-D	4.65 ... 5.50 $\mu\text{mol/s}$	Q65115A3131
GW PUBRA1.HW-S5T3-M4-1-D	4.65 ... 5.70 $\mu\text{mol/s}$	Q65115A3130
GW PUBRA1.HW-S5T3-M5-1-D	4.65 ... 5.70 $\mu\text{mol/s}$	Q65115A3129
GW PUBRA1.HW-S6T3-M6-1-D	4.80 ... 5.70 $\mu\text{mol/s}$	Q65115A3128

## Maximum Ratings

Parameter	Symbol	Values	
Operating Temperature	$T_{op}$	min.	-40 °C
		max.	125 °C
Storage Temperature	$T_{stg}$	min.	-40 °C
		max.	125 °C
Junction Temperature	$T_j$	max.	135 °C
Forward current	$I_F$	min.	100 mA
		max.	2000 mA
Surge Current $t \leq 10 \mu\text{s}$ ; $D = 0.005$ ; $T_j = 85 \text{ }^\circ\text{C}$	$I_{FS}$	max.	2500 mA
Reverse voltage <sup>2)</sup>	$V_R$	Not designed for reverse operation	
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)	$V_{ESD}$	8 kV	

## Characteristics

$I_F = 700 \text{ mA}$ ;  $T_J = 85 \text{ }^\circ\text{C}$

Parameter	Symbol	Values	
Viewing angle at 50% $I_V$	$2\phi$	typ.	140 °
Forward Voltage <sup>3)</sup> $I_F = 700 \text{ mA}$	$V_F$	min. typ. max.	2.75 V 2.83 V 2.95 V
Reverse current <sup>2)</sup>	$I_R$	Not designed for reverse operation	
Electrical thermal resistance junction/solderpoint with efficiency $\eta_e = 57.5 \text{ \%}$	$R_{thJS \text{ elec.}}$	typ.	1.8 K / W

## Brightness Groups

Group	Photon Flux <sup>1)</sup> PF/W			Total Radiant Flux min. $\Phi_E$	Total Radiant Flux max. $\Phi_E$
	$I_F = 700$ mA min. $\Phi_P$	$I_F = 700$ mA max. $\Phi_P$	typ. $\Phi_P$		
S5	4.65 $\mu\text{mol/s}$	4.80 $\mu\text{mol/s}$	2.39 $\mu\text{mol/J}$	1,055 mW	1,089 mW
S6	4.80 $\mu\text{mol/s}$	4.95 $\mu\text{mol/s}$	2.46 $\mu\text{mol/J}$	1,089 mW	1,123 mW
S7	4.95 $\mu\text{mol/s}$	5.10 $\mu\text{mol/s}$	2.54 $\mu\text{mol/J}$	1,123 mW	1,157 mW
T1	5.10 $\mu\text{mol/s}$	5.30 $\mu\text{mol/s}$	2.62 $\mu\text{mol/J}$	1,157 mW	1,202 mW
T2	5.30 $\mu\text{mol/s}$	5.50 $\mu\text{mol/s}$	2.73 $\mu\text{mol/J}$	1,202 mW	1,248 mW
T3	5.50 $\mu\text{mol/s}$	5.70 $\mu\text{mol/s}$	2.83 $\mu\text{mol/J}$	1,248 mW	1,293 mW

Note: [\*] Photon Flux includes wavelengths between 280 and 800 nm.


Note: [\*\*] Radiant Flux values are for reference only.

Note: [\*\*\*] Brightness groups are applicable for M3 bin.

## Forward Voltage Groups

Group	Forward Voltage <sup>3)</sup> $I_F = 700$ mA min. $V_F$	Forward Voltage <sup>3)</sup> $I_F = 700$ mA max. $V_F$
1W	2.75 V	2.80 V
1Y	2.80 V	2.85 V
1Z	2.85 V	2.90 V
2A	2.90 V	2.95 V

## Chromaticity Coordinate Groups <sup>4)</sup>



## Chromaticity Coordinate Groups

Group	Cx	Cy	Group	Cx	Cy	Group	Cx	Cy
M1	0.3184	0.4822	M3	0.2834	0.3861	M5	0.2484	0.2901
	0.3391	0.4747		0.3041	0.3786		0.2691	0.2825
	0.3216	0.4266		0.2866	0.3306		0.2516	0.2345
	0.3009	0.4342		0.2659	0.3381		0.2309	0.2421
M2	0.3009	0.4342	M4	0.2659	0.3381	M6	0.2309	0.2421
	0.3216	0.4266		0.2866	0.3306		0.2516	0.2345
	0.3041	0.3786		0.2691	0.2825		0.2341	0.1865
	0.2834	0.3861		0.2484	0.2901		0.2134	0.1940

---


**Group Name on Label**

**Example: S5-M1-1W**

Brightness	Color Chromaticity	Forward Voltage
S5	M1	1W


## Relative Spectral Emission <sup>5)</sup>

$I_{\text{rel}} = f(\lambda)$ ;  $I_F = 700 \text{ mA}$ ;  $T_J = 85 \text{ }^\circ\text{C}$




## Radiation Characteristics <sup>5)</sup>

$I_{\text{rel}} = f(\varphi)$ ;  $T_J = 85 \text{ }^\circ\text{C}$




**Forward current <sup>5)</sup>**

$I_F = f(V_F)$ ;  $T_J = 85^\circ\text{C}$




**Relative Photon Flux <sup>5), 6)</sup>**

$\Phi_P/\Phi_{P(700\text{ mA})} = f(I_F)$ ;  $T_J = 85^\circ\text{C}$




**Chromaticity Coordinate Shift <sup>5)</sup>**

$\Delta Cx, \Delta Cy = f(I_F)$ ;  $T_J = 85^\circ\text{C}$




### Forward Voltage <sup>5)</sup>

$$\Delta V_F = V_F - V_F(85^\circ\text{C}) = f(T_j); I_F = 700 \text{ mA}$$




### Relative Photon Flux <sup>5)</sup>

$$\Phi_p/\Phi_p(85^\circ\text{C}) = f(T_j); I_F = 700 \text{ mA}$$




### Chromaticity Coordinate Shift <sup>5)</sup>

$$\Delta Cx, \Delta Cy = f(T_j); I_F = 700 \text{ mA}$$






## Max. Permissible Forward Current <sup>7)</sup>

$$I_F = f(T)$$



Dimensional Drawing <sup>8)</sup>



General tolerance  $\pm 0.1$

Lead finish Au


C69062-A0052-A4..-01

Further Information:

Approximate Weight: 44.0 mg

ESD advice: The device is protected by ESD device which is connected in parallel to the Chip.


**Recommended Solder Pad 8)**



For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for ultra sonic cleaning.

## Reflow Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E




Profile Feature	Symbol	Pb-Free (SnAgCu) Assembly			Unit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat*) 25 °C to 150 °C			2	3	K/s
Time $t_s$ $T_{Smin}$ to $T_{Smax}$	$t_s$	60	100	120	s
Ramp-up rate to peak*) $T_{Smax}$ to $T_p$			2	3	K/s
Liquidus temperature	$T_L$	217			°C
Time above liquidus temperature	$t_L$	80	100	100	s
Peak temperature	$T_p$	245	260	260	°C
Time within 5 °C of the specified peak temperature $T_p$ - 5 K	$t_p$	10	20	30	s
Ramp-down rate* $T_p$ to 100 °C			3	6	K/s
Time 25 °C to $T_p$			480	480	s

All temperatures refer to the center of the package, measured on the top of the component


\* slope calculation  $DT/Dt$ :  $Dt$  max. 5 s; fulfillment for the whole T-range

Taping <sup>8)</sup>



C69062-A0052-B8-02


**Tape and Reel** <sup>9)</sup>



**Reel Dimensions**


A	W	$N_{\min}$	$W_1$	$W_{2\max}$	Pieces per PU
330 mm	12 + 0.3 / - 0.1 mm	60 mm	12.4 + 2 mm	18.4 mm	3000

## Barcode-Product-Label (BPL)



OHA04563

## Dry Packing Process and Materials



OHA00539

Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according to JEDEC-STD-033.

## Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **moderate risk (exposure time 0.25 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

This device is designed for specific/recommended applications only. Please consult OSRAM Opto Semiconductors Sales Staff in advance for detailed information on other non-recommended applications (e.g. automotive).

Change management for this component is aligned with the requirements of the lighting market.

For further application related information please visit <https://ams-osram.com/support/application-notes>

## Disclaimer

### Attention please!

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.  
If printed or downloaded, please find the latest version on our website.

### Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

### Product and functional safety devices/applications or medical devices/applications

Our components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

Our products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using our components in product safety devices/applications or medical devices/applications, buyer and/or customer has to inform our local sales partner immediately and we and buyer and /or customer will analyze and coordinate the customer-specific request between us and buyer and/or customer.

## Glossary

- 1) **Brightness:** Brightness values are measured during a current pulse of typically 10 ms, with a tolerance of +/- 7%.
- 2) **Reverse Operation:** Not designed for reverse operation. Continuous reverse operation can cause migration and damage of the device.
- 3) **Forward Voltage:** The Forward voltage is measured during a current pulse duration of typically 1 ms with a tolerance of  $\pm 0.05V$ .
- 4) **Chromaticity coordinate groups:** Chromaticity coordinate groups are measured during a current pulse duration of typically 10ms with a tolerance of  $\pm 0.005$ .
- 5) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 6) **Characteristic curve:** In the range where the line of the graph is broken, you must expect higher differences between single devices within one packing unit.
- 7) **Thermal Resistance:**  $R_{th\ max}$  is based on statistic values ( $6\sigma$ ) used for Derating.
- 8) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with  $\pm 0.1$  and dimensions are specified in mm.
- 9) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

## Revision History

Version	Date	Change
1.0	2026-02-09	Initial Version



EU RoHS and China RoHS compliant product

此产品符合欧盟 RoHS 指令的要求；

按照中国的相关法规和标准，

不含有毒有害物质或元素。

**Published by ams-OSRAM AG**

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0

[ams-osram.com](http://ams-osram.com)

© All rights reserved

**am**  **OSRAM**