


LE RTDUW S2W

OSRAM OSTAR® Stage

Compact lightsource in SMT technology, glass window on top, RoHS compliant



Applications

- Architecture
- Mood Lighting
- Stage Lighting (LED & Laser)

Features:

- Package: compact lightsource in multi chip SMT technology with glass window on top
- Chip technology: Thinfilm / ThinGaN
- Typ. Radiation: 120° (Lambertian emitter)
- Color: $\lambda_{\text{dom}} = 625 \text{ nm}$ (● red); $\lambda_{\text{dom}} = 527 \text{ nm}$ (● true green); $\lambda_{\text{dom}} = 453 \text{ nm}$ (● deep blue); Cx = 0.31, Cy = 0.32 acc. to CIE 1931 (● ultra white)
- Corrosion Robustness Class: 3B
- ESD: 2 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)

Ordering Information

Type	Brightness ¹⁾	Ordering Code
LE RTDUW S2W		Q65111A0884
● red	● $\Phi_V = 45 \dots 112 \text{ lm}$ ($I_F = 700 \text{ mA}$)	
● true green	● $\Phi_V = 90 \dots 180 \text{ lm}$ ($I_F = 700 \text{ mA}$)	
● deep blue	● $\Phi_E = 630 \dots 900 \text{ mW}$ ($I_F = 700 \text{ mA}$)	
● ultra white	● $\Phi_V = 140 \dots 224 \text{ lm}$ ($I_F = 700 \text{ mA}$)	

Maximum Ratings

Parameter	Symbol		Values	Values	Values	Values
			● red	● true green	● deep blue	● ultra white
Operating Temperature	T_{op}	min.	-40 °C	-40 °C	-40 °C	-40 °C
		max.	85 °C	85 °C	85 °C	85 °C
Storage Temperature	T_{stg}	min.	-40 °C	-40 °C	-40 °C	-40 °C
		max.	85 °C	85 °C	85 °C	85 °C
Junction Temperature	T_j	max.	125 °C	125 °C	125 °C	125 °C
Forward Current $T_s = 25\text{ °C}$	I_F	min.	100 mA	100 mA	100 mA	100 mA
		max.	1000 mA	1000 mA	1000 mA	1000 mA
ESD withstand voltage acc. to ANSI/ESDA/ JEDEC JS-001 (HBM, Class 2)	V_{ESD}		2 kV	2 kV	2 kV	2 kV
Reverse current ²⁾	I_R	max.	200 mA	200 mA	200 mA	200 mA

Characteristics

 $I_F = 700 \text{ mA}; T_S = 25 \text{ }^\circ\text{C}$

Parameter	Symbol		Values ● red	Values ● true green	Values ● deep blue	Values ● ultra white
Chromaticity Coordinate						0.31 0.32
Peak Wavelength	λ_{peak}	typ.	632 nm	520 nm	449 nm	
Dominant Wavelength ³⁾	λ_{dom}	min. typ. max.	620 nm 625 nm 632 nm	521 nm 527 nm 533 nm	449 nm 453 nm 457 nm	
Spectral bandwidth at 50% $I_{\text{rel,max}}$	$\Delta\lambda$	typ.	18 nm	33 nm	25 nm	
Viewing angle at 50% I_V	2ϕ	typ.	120 °	120 °	120 °	120 °
Radiating surface For value(s) see red column, all chips operated simultaneously	A_{color}	typ.	2.1 x 2.1 m ²			
Partial Flux acc. CIE 127:2007 ⁴⁾ $\Phi_{E/V \ 120^\circ} = x * \Phi_{E/V \ 180^\circ}$	$\Phi_{E/V, \ 120^\circ}$	typ.	0.82	0.82	0.82	0.82
Forward Voltage ⁵⁾ $I_F = 700 \text{ mA}$	V_F	min. typ. max.	2.10 V 2.50 V 2.90 V	2.90 V 3.60 V 4.20 V	2.90 V 3.45 V 4.00 V	2.90 V 3.45 V 4.00 V
Reverse voltage (ESD device)	$V_{R \text{ ESD}}$	min.	5 V	5 V	5 V	5 V
Reverse voltage ²⁾ $I_R = 20 \text{ mA}$	V_R	max.	1.2 V	1.2 V	1.2 V	1.2 V
Real thermal resistance junction/solderpoint ⁶⁾ For value(s) see red column, all chips operated simultaneously	$R_{\text{thJS real}}$	typ. max.	1.8 K / W 2.3 K / W			
Electrical thermal resistance junction/solderpoint ⁶⁾ With efficiency $\eta_e = 23\%$; for value(s) see red column, all chips operated simultaneously	$R_{\text{thJS elec.}}$	typ. max.	1.4 K / W 1.8 K / W			

Brightness Groups

Color of emission	Group	Luminous Flux ¹⁾ $I_F = 700 \text{ mA}$ min. Φ_V	Luminous Flux ¹⁾ $I_F = 700 \text{ mA}$ max. Φ_V
• red	JA	45 lm	56 lm
• red	JB	56 lm	71 lm
• red	KA	71 lm	90 lm
• red	KB	90 lm	112 lm
• true green	KB	90 lm	112 lm
• true green	LA	112 lm	140 lm
• true green	LB	140 lm	180 lm
• deep blue	4U	630 mW	710 mW
• deep blue	1V	710 mW	800 mW
• deep blue	2V	800 mW	900 mW
• ultra white	LB	140 lm	180 lm
• ultra white	MA	180 lm	224 lm

Wavelength Groups

- true green


Group	Dominant Wavelength ³⁾ min. λ_{dom}	Dominant Wavelength ³⁾ max. λ_{dom}
3	521 nm	527 nm
4	527 nm	533 nm

Wavelength Groups

- deep blue

Group	Dominant Wavelength ³⁾ min. λ_{dom}	Dominant Wavelength ³⁾ max. λ_{dom}
3	449 nm	453 nm
4	453 nm	457 nm

Chromaticity Coordinate Groups




Chromaticity Coordinate Groups

- ultra white

Group	Cx	Cy
CQ	0.3190	0.3507
	0.3267	0.3370
	0.3107	0.3043
	0.3020	0.3178


Relative Spectral Emission ⁴⁾

$$\Phi_{\text{rel}} = f(\lambda); I_F = 700 \text{ mA}; T_J = 25^\circ\text{C}$$




Radiation Characteristics ⁴⁾

$$I_{\text{rel}} = f(\phi); T_J = 25^\circ\text{C}$$




Relative Partial Flux ⁴⁾

$$\Phi_{V/E}(2\varphi)/\Phi_{V/E}(180^\circ) = f(\varphi); T_J = 25^\circ\text{C}$$




Forward current ^{4), 7)}


$$I_F = f(V_F); T_J = 25\text{ °C}$$

**Forward current** ^{4), 7)}


$$I_F = f(V_F); T_J = 25\text{ °C}$$

**Forward current** ^{4), 7)}

$$I_F = f(V_F); T_J = 25\text{ °C}$$


**Forward current** ^{4), 7)}

$$I_F = f(V_F); T_J = 25\text{ °C}$$




Relative Luminous Flux ^{4), 7)}


$$\Phi_V / \Phi_V(700 \text{ mA}) = f(I_F); T_J = 25^\circ \text{C}$$

**Relative Luminous Flux** ^{4), 7)}


$$\Phi_V / \Phi_V(700 \text{ mA}) = f(I_F); T_J = 25^\circ \text{C}$$

**Relative Radiant Power** ^{4), 7)}

$$\Phi_E / \Phi_E(700 \text{ mA}) = f(I_F); T_J = 25^\circ \text{C}$$


**Relative Luminous Flux** ^{4), 7)}

$$\Phi_V / \Phi_V(700 \text{ mA}) = f(I_F); T_J = 25^\circ \text{C}$$




Dominant Wavelength ⁴⁾


$$\Delta\lambda_{\text{dom}} = f(I_F); T_J = 25\text{ °C}$$

Dominant Wavelength ⁴⁾

$$\Delta\lambda_{\text{dom}} = f(I_F); T_J = 25\text{ °C}$$


Chromaticity Coordinate Shift ⁴⁾

$$\Delta Cx, \Delta Cy = f(I_F); T_J = 25\text{ °C}$$




Forward Voltage ⁴⁾


$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 700\text{ mA}$$

**Forward Voltage** ⁴⁾


$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 700\text{ mA}$$

**Forward Voltage** ⁴⁾

$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 700\text{ mA}$$


**Forward Voltage** ⁴⁾

$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 700\text{ mA}$$




Relative Luminous Flux ⁴⁾


$$\Phi_V / \Phi_V(25^\circ\text{C}) = f(T_j); I_F = 700\text{ mA}$$

**Relative Luminous Flux** ⁴⁾


$$\Phi_V / \Phi_V(25^\circ\text{C}) = f(T_j); I_F = 700\text{ mA}$$

**Relative Radiant Power** ⁴⁾

$$\Phi_E / \Phi_E(25^\circ\text{C}) = f(T_j); I_F = 700\text{ mA}$$


**Relative Luminous Flux** ⁴⁾

$$\Phi_V / \Phi_V(25^\circ\text{C}) = f(T_j); I_F = 700\text{ mA}$$




Dominant Wavelength ⁴⁾


$$\Delta\lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25^\circ\text{C}) = f(T_j); I_F = 700 \text{ mA}$$

**Dominant Wavelength** ⁴⁾


$$\Delta\lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25^\circ\text{C}) = f(T_j); I_F = 700 \text{ mA}$$

**Dominant Wavelength** ⁴⁾

$$\Delta\lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25^\circ\text{C}) = f(T_j); I_F = 700 \text{ mA}$$


**Chromaticity Coordinate Shift** ⁴⁾

$$\Delta Cx, \Delta Cy = f(T_j); I_F = 700 \text{ mA}$$




Max. Permissible Forward Current

$I_F = f(T_S)$; for 4 Chip operated



Dimensional Drawing ⁸⁾



C63062-A4028-A1...-09


Further Information:

Approximate Weight: 66.0 mg

Corrosion test: Class: 3B
 Test condition: 40°C / 90 % RH / 15 ppm H₂S / 14 days (stricter than IEC 60068-2-43)


ESD advice: The device is protected by ESD device which is connected in parallel to the Chip.

Electrical Internal Circuit



Pin	Description
Pin 1	Cathode Chip 1 (red)
Pin 2	Anode Chip 1 (red)
Pin 3	Cathode Chip 2 (true green)
Pin 4	Anode Chip 2 (true green)
Pin 5	Cathode Chip 3 (deep blue)
Pin 6	Anode Chip 3 (deep blue)
Pin 7	Cathode Chip 4 (ultra white)
Pin 8	Anode Chip 4 (ultra white)

Recommended Solder Pad ⁸⁾




E062 3010.76 -01

For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for any kind of wet cleaning or ultrasonic cleaning.

Reflow Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E




Profile Feature	Symbol	Pb-Free (SnAgCu) Assembly			Unit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat ^{*)} 25 °C to 150 °C			2	3	K/s
Time t_s T_{Smin} to T_{Smax}	t_s	60	100	120	s
Ramp-up rate to peak ^{*)} T_{Smax} to T_p			2	3	K/s
Liquidus temperature	T_L		217		$^{\circ}\text{C}$
Time above liquidus temperature	t_L		80	100	s
Peak temperature	T_p		245	260	$^{\circ}\text{C}$
Time within 5 °C of the specified peak temperature $T_p - 5\text{ K}$	t_p	10	20	30	s
Ramp-down rate* T_p to 100 °C			3	6	K/s
Time 25 °C to T_p				480	s

All temperatures refer to the center of the package, measured on the top of the component


* slope calculation DT/Dt : Dt max. 5 s; fulfillment for the whole T-range

Taping ⁸⁾



C63062-A3985-B7-03


Tape and Reel ⁹⁾




Reel Dimensions

A	W	N _{min}	W ₁	W _{2 max}	Pieces per PU
180 mm	12 + 0.3 / - 0.1 mm	60 mm	12.4 + 2 mm	18.4 mm	500

Barcode-Product-Label (BPL)

OSRAM Opto Semiconductors		LX XXXX	BIN1: XX-XX-X-XXX-X		
(6P) BATCH NO:	1234567890	RoHS Compliant			
		 ML Temp ST X XXX °C X			
(1T) LOT NO:	1234567890	(9D) D/C:		1234	
		Pack: RXX DEMY XXX X_X123_1234.1234 X			
(X) PROD NO:	123456789	(Q) QTY:	9999	(G) GROUP:	XX-XX-X-X
					


Dry Packing Process and Materials ⁸⁾



Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according JEDEC-STD-033.



Type Designation System



Discontinued

Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet falls into the class **moderate risk (exposure time 0.25 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

For further application related information please visit www.osram-os.com/appnotes

Disclaimer

Attention please!

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.

If printed or downloaded, please find the latest version on the OSRAM OS website.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product and functional safety devices/applications or medical devices/applications

OSRAM OS components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

OSRAM OS products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using OSRAM OS components in product safety devices/applications or medical devices/applications, buyer and/or customer has to inform the local sales partner of OSRAM OS immediately and OSRAM OS and buyer and /or customer will analyze and coordinate the customer-specific request between OSRAM OS and buyer and/or customer.

Glossary

- 1) **Brightness:** Brightness values are measured during a current pulse of typically 25 ms, with an internal reproducibility of $\pm 8\%$ and an expanded uncertainty of $\pm 11\%$ (acc. to GUM with a coverage factor of $k = 3$).
- 2) **Reverse Operation:** This product is intended to be operated applying a forward current within the specified range. Applying any continuous reverse bias or forward bias below the voltage range of light emission shall be avoided because it may cause migration which can change the electro-optical characteristics or damage the LED.
- 3) **Wavelength:** The wavelength is measured at a current pulse of typically 25 ms, with an internal reproducibility of ± 0.5 nm and an expanded uncertainty of ± 1 nm (acc. to GUM with a coverage factor of $k = 3$).
- 4) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 5) **Forward Voltage:** The forward voltage is measured during a current pulse of typically 8 ms, with an internal reproducibility of ± 0.05 V and an expanded uncertainty of ± 0.1 V (acc. to GUM with a coverage factor of $k = 3$).
- 6) **Thermal Resistance:** $R_{th\ max}$ is based on statistic values (6σ).
- 7) **Characteristic curve:** In the range where the line of the graph is broken, you must expect higher differences between single devices within one packing unit.
- 8) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ± 0.1 and dimensions are specified in mm.
- 9) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

Revision History

Version	Date	Change
1.2	2018-11-28	Characteristics
1.3	2020-06-03	Schematic Transportation Box Dimensions of Transportation Box
1.4	2020-07-07	Characteristics
1.5	2020-07-08	Discontinued
1.5	2020-07-15	Discontinued

Published by OSRAM Opto Semiconductors GmbH
Leibnizstraße 4, D-93055 Regensburg
www.osram-os.com © All Rights Reserved.

EU RoHS and China RoHS compliant product



此产品符合欧盟 RoHS 指令的要求；
按照中国的相关法规和标准，不含有毒有害物质或元素。